

C-BAND	Application																	
	Item	unit	Comment	Fixed, central station (high powered)		VSAT		SNG			Maritime				Mobile, non maritime			Small diameter, On-The-Move Terminals, Atypical Construction, Advanced Technology
Diameter	(m)			D >= 4.5	4.5 > D > 1.2	4.5 > D >= 2.4	2.4 > D >= 1.2	D > 2.4	2.4 >= D >= 1.2	D < 1.2	> 4.5	4.5 > D >= 2.4	2.4 > D >= 1.2	D < 1.2	n/a	n/a	n/a	
Diameter equivalent to	(m)			n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	D >= 1.2	1.2 > D >= 0.8	D < 0.8	The corresponding / adequate equivalent diameter with reference to antenna gain in the direction towards the satellite can be used for link analysis. For low profile and flat antennas, D is the smaller dimension of the aperture as it is projected to the satellite direction.
D/λ			Reference frequency 6.025 GHz	D/λ >= 90	D/λ < 90	90.4 > D/λ >= 48.2	48.2 > D/λ >= 24.1	D/λ > 48.2	48.2 >= D/λ >= 24.1	D/λ < 24	D/λ > 90	90.4 > D/λ >= 48.2	48.2 > D/λ >= 24.1	D/λ < 24.1	D/λ >= 24.1	24.1 > D/λ >= 16.1	D/λ < 16.1	
Antenna sidelobe characteristics (aligned to geostationary arc)			Range end: +/- 9 deg. for each of the given off-axis gain requirements, 10% of the side-lobes are permitted to exceed the indicated mask with a maximum of 3 dB - Please indicate mask with chosen specification (FCC, ITU, ETSI etc.)	29 - 25 log (θ)	38 - 25 log (θ)	29 - 25 log (θ)	38 - 25 log (θ)	29 - 25 log (θ)	38 - 25 log (θ)	39 - 25 log	29 - 25 log (θ)	38 - 25 log (θ)	39 - 25 log (θ)	39.5 - 25 log (θ)	39 - 25 log (θ)	40 - 25 log (θ)	40 - 25 log (θ)	Parameter evaluation on a Case-By-Case basis by individual satellite operators, based on the ITU Today adjacent satellite coordination process as defined in Article 9 of the Radio Regulations (RR), and the 6% delta T/T threshold for non-conformal antennas
Measured Co-polar pattern - with radome if applicable (low-mid-end high frequency band) - At least one frequency in the operational band			Antenna Gain patterns	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"
Starts at α	(Deg)		Definition of starting point	α = greater (1.0, 100°/λ/D)		α = greater (1.0, 100°/λ/D)		α = greater (1.0, 100°/λ/D)			α = greater (1.0, 100°/λ/D)				α = greater (1.0, 100°/λ/D)			Parameter evaluation on a Case-By-Case basis by individual satellite operators, dependent on application and operational environment
X-pol isolation within 1 dB contour - linear polarization	(dB)		Individual satellite operator could implement lower values in exceptional circumstances with E.I.R.P. restrictions	25	25	25	25	25	25	25	25	25	25	18	18	18	18	18
X-pol isolation within 1 dB contour - circular polarization	(dB)		Individual satellite operator could implement lower values in exceptional circumstances with E.I.R.P. restrictions	18	18	18	18	18	18	18	22	22	22	15	18	15	15	15
Measured Cross-polar pattern			Antenna patterns to be provided with radome if applicable - transmit and receive	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"
Polarization Alignment Accuracy				within 1°	within 1°	within 1°	within 2°	within 1°	within 1°	within 3°	within 1°	within 1°	within 1°	within 5°	within 5°	within 5°	within 5°	within 5°
Azimuth / Elevation fine adjustment mechanics			Mis-pointing must cause less than 1 dB reduction of carrier EIRP towards satellite	n/a	to reduce mispointing to 0.5 deg	to reduce mispointing to 0.5 deg	to reduce mispointing to 0.5 deg	to reduce mispointing to 0.5 deg	to reduce mispointing to 0.5 deg	to reduce mispointing to 0.5 deg	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Tracking (mandatory)				yes	n/a	n/a	n/a	n/a	n/a	n/a	yes	yes	yes	yes	yes	yes	yes	yes
Structural Stability				picture required		picture required		picture required			picture required				picture required			picture required
Windload Operational			Wind speed for maximum 3 dB reduction of carrier EIRP towards satellite	55 km/h	55 km/h	55 km/h	55 km/h	55 km/h	55 km/h	55 km/h	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Min/max temp	(deg C)		Unit reflector should be able to sustain these temperatures for multiple hours	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	n/a	n/a	n/a	n/a	According to equipment specification for aircraft, land-mobile, rail and maritime	According to equipment specification for aircraft, land-mobile, rail and maritime	According to equipment specification for aircraft, land-mobile, rail and maritime	According to equipment specification for aircraft, land-mobile, rail and maritime
Investigate the possible influence on the antenna pattern introduced by the de-icing			Highly recommended	yes	yes	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Installation of an Antenna Control Unit				Mandatory	Recommended	n/a	n/a	Recommended	Recommended	Recommended	Mandatory in antenna system	Mandatory in antenna system	Mandatory in antenna system	Mandatory in antenna system	Mandatory in antenna system	Mandatory in antenna system	Mandatory in antenna system	Mandatory in antenna system
To issue a look-up table for polarization / skew angle off-set to the antenna operator			Special antenna types	n/a	n/a	n/a	n/a	yes	yes	yes	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Maximum deviation from direction to satellite	(deg)		Angle determined by maximum 3 dB reduction of carrier EIRP towards satellite	n/a	n/a	n/a	n/a	n/a	n/a	n/a	Applicable	Applicable	Applicable	Applicable	Applicable	Applicable	Applicable, only 1 dB max. carrier reduction	Applicable, only 1 dB max. carrier reduction
Software may not be modifiable by operator			SNG's and mobile, auto-acquiring On-The-Move systems only - This includes data for the tracking mechanism, the acquisition, for mis-pointing and power levels to the antenna flange etc. It includes any unit where software is installed, like BUC, modem and ACU, or other components	n/a	n/a	n/a	n/a	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Radome in production must be identical to the radome with which the antenna system has been tested				n/a	n/a	n/a	n/a	n/a	n/a	n/a	yes	yes	yes	yes	yes - n/a for airborne antennas	yes - n/a for airborne antennas	yes - n/a for airborne antennas	yes - n/a for airborne antennas
Antenna Tx Gain at mid band frequency	(dBi)		For information only	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Antenna Tx frequency range	(GHz)		For information only	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Spurious Emissions (Carrier Off)			Shall not exceed 4dBW/4KHz	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable
Transmit E.I.R.P. indicator	(dB)		At discretion of individual satellite operator	yes	yes	n/a	n/a	yes	yes	yes	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Maximum E.I.R.P. rating	(dBW)		Required value from every manufacturer	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
E.I.R.P. Adjustment Resolution in the Full Range of HPA power	(dB)			0.5	0.5	recommended	recommended	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	
E.I.R.P. stability	(dB)		Integrated into antenna system mobile/maritime	n/a	n/a	n/a	n/a	n/a	n/a	n/a	1	1	1	1	1	1	1	1
Automatic carrier mute, mandatory if mispointing exceeds			mobile, auto-acquiring On-The-Move systems only	n/a	n/a	n/a	n/a	n/a	n/a	n/a	+/- 0.5°	+/- 0.5°	+/- 0.5°	+/- 0.5°	+/- 0.5°	+/- 0.5°	+/- 0.5°	+/- 0.5°
Time within which the automatic carrier mute will have to take place	(ms)		mobile, auto-acquiring On-The-Move systems only	n/a	n/a	n/a	n/a	n/a	n/a	n/a	100 ms	100 ms	100 ms	100 ms	100 ms	100 ms	100 ms	100 ms
Transmission to resume at (or less than) angle	(deg)		mobile, auto-acquiring On-The-Move systems only	n/a	n/a	n/a	n/a	n/a	n/a	n/a	± 0.2 within 1 sec	± 0.2 within 1 sec	± 0.2 within 1 sec	± 0.2 within 1 sec	± 0.2 within 1 sec	± 0.2 within 1 sec	± 0.2 within 1 sec	± 0.2 within 1 sec
Transmit earth stations must be equipped with a receive chain which allows pointing optimization and tracking prior to and during transmissions				yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Antenna RX gain at mid band frequency	(dB)		For information only	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Antenna RX frequency range	(GHz)		For information only	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Add G/T values	(dB/K)		G/T referred to LNB input at 20° Elevation at 25°C (additional testing required at 10°C and 40°C) ambient temperature: Mid-Band Gain figure to be used Measurements includes OMIT/Polarizer losses, for information only	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
General Remark	The individual satellite companies participating in this certification process are subject to trade control and sanctions laws that may restrict their ability to review and approve equipment proposed by certain vendors.																	

Item	unit	Comment	Application																
			Fixed, central station (high powered)		VSAT			SNG			Maritime			Small diameter, On-The-Move Terminals, Atypical Construction, Advanced Technology					
Diameter	(m)		D >= 3.8	3.8 > D >= 1.8	3.8 > D >= 1.5	1.5 > D >= 1.0	D < 1.0	3.8 > D >= 1.5	1.5 > D >= 1.0	D < 1.0	3.8 > D >= 1.5	1.5 > D >= 1.0	D < 1.0	n/a	n/a	non-parabolic, non-maritime			
Diameter equivalent to			n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	D >= 0.6 m	D < 0.6 m	The corresponding / adequate equivalent diameter with reference to antenna gain in the direction towards the satellite can be used for link analysis. For low profile and flat antennas, D is the smaller dimension of the aperture as it is projected to the satellite direction.			
D/A		Reference frequency 14-250 GHz	D/A >= 180.6	180.6 > D/A >= 85.6	180 > D/A >= 71.3	71.3 > D/A >= 47.5	D/A < 47.5	180 > D/A >= 71.3	71.3 > D/A >= 47.5	D/A < 47.5	180 > D/A >= 71.3	71.3 > D/A >= 47.5	D/A < 47.5	D/A >= 28.53	D/A < 28.53	Parameter evaluation on a Case-By-Case basis by individual satellite operators, based on the ITU Today adjacent satellite coordination process as defined in Article 9 of the Radio Regulations (RR), and the 95% delta T/T threshold for non-conformal antennas.			
Antenna side-lobe characteristics (aligned to geostationary arc)		Range end: +/- 9 deg, for each of the given off-axis gain requirements, 10% of the side-lobes are permitted to exceed the indicated mask by a maximum of 3 dB - Please indicate mask with chosen specification (FCC, ITU, ETS etc.)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	Parameter evaluation on a Case-By-Case basis by individual satellite operators, dependent on application and operational environment		
Measured Co-polar pattern - with radome if applicable (low, mid and high frequency band) At least one frequency in the operational band		Antenna Gain patterns	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"
Starts at α	(Deg)	Definition of starting point	α = greater (1.0, 100°/D)		α = greater (1.0, 100°/D)			α = greater (1.0, 100°/D)			α = greater (1.0, 100°/D)			α = greater (1.0, 100°/D)					
X-pol isolation within 1 dB contour - linear polarization	(dB)	Individual satellite operator could implement lower values in exceptional circumstances with E.I.R.P. restrictions	25	25	25	25	25	25	25	25	25	25	25	25	25	25	20		
X-pol isolation within 1 dB contour - circular polarization	(dB)	Individual satellite operator could implement lower values in exceptional circumstances with E.I.R.P. restrictions	25	25	25	25	25	25	25	25	25	25	25	20	18	18			
Measured Cross-polar pattern		Antenna patterns to be provided with radome if applicable - transmit and receive	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"
Polarization Alignment Accuracy			within 1°	within 1°	within 1°	within 1°	within 1°	within 1°	within 1°	within 1°	within 1°	within 1°	within 1°	within 1°	within 1°	within 1°			
Azimuth / Elevation fine adjustment mechanics		Mis-pointing must cause less than 1 dB reduction of carrier EIRP towards satellite	n/a	yes	to reduce mispointing to 0.5 deg	to reduce mispointing to 0.5 deg	to reduce mispointing to 0.5 deg	to reduce mispointing to 0.5 deg	to reduce mispointing to 0.5 deg	to reduce mispointing to 0.5 deg	n/a	n/a	n/a	n/a	n/a	n/a			
Tracking (mandatory)			yes	n/a	n/a	n/a	n/a	n/a	n/a	n/a	yes	yes	yes	yes	yes	yes			
Structural Stability			picture required	picture required	picture required	picture required	picture required	picture required	picture required	picture required	picture required	picture required	picture required	picture required	picture required	picture required			
Windload operational	(km/h)	Wind speed for maximum 3 dB reduction of carrier EIRP towards satellite	55 km/h	55 km/h	55 km/h	55 km/h	55 km/h	55 km/h	55 km/h	55 km/h	n/a	n/a	n/a	n/a	n/a	n/a			
Min/max temp	(deg C)	Unit reflector should be able to sustain these temperatures for multiple hours	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	n/a	n/a	n/a	According to equipment specification for aircraft, land-mobile, rail and maritime		
Investigate the possible influence on the antenna pattern introduced by the de-icing		Highly recommended	yes	yes	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	According to equipment specification for aircraft, land-mobile, rail and maritime		
Installation of an Antenna Control Unit			Mandatory	Highly recommended	n/a	n/a	n/a	Highly recommended	Highly recommended	Highly recommended	Mandatory in antenna system	Mandatory in antenna system	Mandatory in antenna system	Mandatory in antenna system	Mandatory in antenna system	Mandatory in antenna system			
To issue a look-up table for polarization / skew angle off-set to the antenna operator		Special antenna types	n/a	n/a	n/a	n/a	n/a	yes	yes	yes	n/a	n/a	n/a	n/a	n/a	n/a			
Maximum deviation from direction to satellite	(deg)	Angle determined by maximum 3 dB reduction of carrier EIRP towards satellite	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	Applicable	Applicable	Applicable	Applicable	Applicable	Applicable, only 1 dB max. carrier reduction			
Software may not be modifiable by operator		SNG's and mobile, auto-acquiring On-The-Move systems only - This includes data for the tracking mechanism, the acquisition, for mis-pointing and power levels to the antenna flange etc. It includes any unit where software is installed, like BUC, modem and ACU, or other components	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	yes	yes	yes			
Radome in production must be identical to the radome with which the antenna system has been tested			n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	yes	yes	yes	yes	yes	yes			
Antenna Tx Gain at mid band frequency	(dB)	For information only	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes			
Antenna Tx Frequency range	(GHz)	For information only	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes			
Spurious Emission (Carrier Off)		Shall not exceed 48dB/4kHz	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable			
Transmit E.I.R.P. indicator	(dB)	At discretion of individual satellite operator	yes	yes	n/a	n/a	n/a	yes	yes	recommended	recommended	recommended	recommended	n/a	n/a	n/a			
Maximum E.I.R.P. rating	(dBW)	Required value from every manufacturer	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes			
E.I.R.P. Adjustment Resolution in the Full Range of HPF power	(dB)		0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5			
E.I.R.P. stability	(dB)	Integrated into antenna system/mobile/maritime	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	1	1	1	1	1	1			
Automatic carrier mute, mandatory if mispointing exceeds	(deg)	mobile, auto-acquiring On-The-Move systems only	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	+/- 0.5°	+/- 0.5°	+/- 0.5°	+/- 0.5°	+/- 0.5°	+/- 0.5°			
Time within which the automatic carrier mute will have to take place	(ms)	mobile, auto-acquiring On-The-Move systems only	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	100 ms	100 ms	100 ms	100 ms	100 ms	100 ms			
Transmission to resume at (or less than) angle	(deg)	mobile, auto-acquiring On-The-Move systems only	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	± 0.2 within 1 sec	± 0.2 within 1 sec	± 0.2 within 1 sec	± 0.2 within 1 sec	± 0.2 within 1 sec	± 0.2 within 1 sec			
Transmit earth stations must be equipped with a receive chain which allows pointing optimization and tracking prior to and during transmissions			yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes			
Antenna RX gain at mid band frequency	(dB)	For information only	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes			
Antenna RX Frequency range	(GHz)	For information only	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes			
Add G/T values	(dB/K)	G/T referred to LNB input at 20° Elevation at 23°C (additional testing required at 10°C and 40°C) ambient temperature. Mid-Band Gain figure to be used Measurements includes OMT/Polarizer losses, for information only	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes			

Transmit specifications for antennas only

Additional TX specification for antennas plus RF electronics (DDU)

Receive specifications

General Remark

The individual satellite companies participating in this certification process are subject to trade control and sanctions laws that may restrict their ability to review and approve equipment proposed by certain vendors.

Item	unit	Comment	Application													Small diameter, On-The-Move Terminals, Atypical Construction, Advanced Technology		
			Fixed, central station (high powered)		VSAT			SNG			Maritime			n/a		n/a		non-parabolic, non-maritime
Diameter	(m)		D >= 3.8	3.8 > D >= 1.8	1.8 > D >= 1.5	1.5 > D >= 1.0	D < 1.0	D > 1.2	1.2 > D >= 0.65	D < 0.65	D > 1.2	1.2 > D >= 0.65	D < 0.65	n/a	n/a	n/a		
Diameter equivalent to			n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	D >= 0.4	D < 0.4	The corresponding / adequate equivalent diameter with reference to antenna gain in the direction towards the satellite can be used for link analysis. For low profile and flat antennas, D is the smaller dimension of the aperture as it is projected to the satellite direction.		
D/λ		Reference frequency 30 GHz	D/λ >= 380.3	380.3 > D/λ >= 180.1	180.1 > D/λ >= 150.1	150.1 > D/λ >= 100.1	D/λ < 100.1	D/λ > 120.1	120.1 > D/λ >= 65	D/λ < 65	D/λ > 120.1	120.1 > D/λ >= 65	D/λ < 65	D/λ >= 40	D/λ < 40			
Antenna sidelobe characteristics (aligned to geostationary arc)		Range end: +/- 9 deg, for each of the given off-axis gain requirements, 10% of the side-lobes are permitted to exceed the indicated mask by a maximum of 3 dB - Please indicate mask with chosen specification (FCC, ITU, ETSI etc.)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	29 - 25 log (θ)	32 - 25 log (θ)	39 - 25 log (θ)	Parameter evaluation on a Case-By-Case basis by individual satellite operators, based on the ITU Today adjacent satellite coordination process as defined in Article 9 of the Radio Regulations (RR), and the 6% delta T/T threshold for non-conformal antennas		
Measured Co-polar pattern - with radome if applicable (low- mid- end high frequency band) . At least one frequency in the operational band		Antenna Gain patterns	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	AZ/EL plots	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"		
Starts at α	(Deg)	Definition of starting point	α = greater (1.0, 100*/λ/D)		α = greater (1.0, 100*/λ/D)			α = greater (1.0, 100*/λ/D)			α = greater (1.0, 100*/λ/D)	α = greater (1.0, 100*/λ/D)	α = greater (1.0, 100*/λ/D)	α = 1 or 100*/λ/D		Parameter evaluation on a Case-By-Case basis by individual satellite operators, dependent on application and operational environment		
X-pol isolation within 1 dB contour - linear polarization	(dB)	Individual satellite operator could implement lower values in exceptional circumstances with E.I.R.P. restrictions	25	25	25	25	25	25	25	25	25	25	25	25	25	20		
X-pol isolation within 1 dB contour - circular polarization	(dB)	Individual satellite operator could implement lower values in exceptional circumstances with E.I.R.P. restrictions	20	20	20	20	20	20	20	20	20	20	20	20	18	18		
Measured Cross-polar pattern		Antenna patterns to be provided with radome if applicable - transmit and receive	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	within 1 dB contour (linear polarisation, only boresight at Circular polarisation)	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"	Mandatory, further explained in section "Mandatory Test Data"		
Polarization Alignment Accuracy (not applicable for circular polarized feed)			within 1°	within 1°	within 1°	within 1°	within 1°	within 1°	within 1°	within 1°	within 1°	within 1°	within 1°	within 1°	within 1°	within 1°		
Azimuth / Elevation fine adjustment mechanics		Mis-pointing must cause less than 1 dB reduction of carrier EIRP towards satellite	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	n/a	n/a	n/a	n/a	n/a	n/a		
Tracking (mandatory)			yes	n/a	n/a	n/a	n/a	n/a	n/a	n/a	yes	yes	yes	yes	yes	yes		
Structural Stability			picture required			picture required			picture required			picture required						
Windload operational	(km/h)	Wind speed for maximum 3 dB reduction of carrier EIRP towards satellite	55 km/h	55 km/h	55 km/h	55 km/h	55 km/h	55 km/h	55 km/h	55 km/h	n/a	n/a	n/a	n/a	n/a	n/a		
Min/max temp	(deg C)	Unit reflector should be able to sustain these temperatures for multiple hours	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	-30 to 50 deg C	n/a	n/a	n/a	According to equipment specification for aircraft, land-mobile, rail and maritime	According to equipment specification for aircraft, land-mobile, rail and maritime	According to equipment specification for aircraft, land-mobile, rail and maritime		
Investigate the possible influence on the antenna pattern introduced by the de-icing		Highly recommended	yes	yes	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a		
Installation of an Antenna Control Unit			Mandatory	Highly recommended	n/a	n/a	n/a	Highly recommended	Highly recommended	Highly recommended	Mandatory in antenna system	Mandatory in antenna system	Mandatory in antenna system	Mandatory in antenna system	Mandatory in antenna system	Mandatory in antenna system		
To issue a look-up table for polarization / skew angle off-set to the antenna operator		Special antenna types	n/a	n/a	n/a	n/a	n/a	yes	yes	yes	n/a	n/a	n/a	n/a	n/a	n/a		
Maximum deviation from direction to satellite	(deg)	Angle determined by maximum 3 dB reduction of carrier EIRP towards satellite	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	Applicable	Applicable	Applicable	Applicable	Applicable	Applicable, only 1 dB max. carrier reduction		
Software may not be modifiable by operator		SNG's and mobile, auto-acquiring On-The-Move systems only - This includes data for the tracking mechanism, the acquisition, for mis-pointing and power levels to the antenna flange etc. It includes any unit where software is installed, like BUC, modem and ACU, or other components	n/a	n/a	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes		
Radome in production must be identical to the radome with which the antenna system has been tested			n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	yes	yes	yes	yes - n/a for airborne antennas	yes - n/a for airborne antennas	yes - n/a for airborne antennas		
Antenna Tx Gain at mid band frequency	(dBi)	For information only	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes		
Antenna Tx frequency range	(GHz)	For information only	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes		
Spurious Emission (Carrier Off)		Shall not exceed 40dBW/4KHz	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable	applicable		
Transmit E.I.R.P. indicator	(dB)	At discretion of individual satellite operator	yes	yes	n/a	n/a	n/a	yes	yes	yes	n/a	n/a	n/a	n/a	n/a	n/a		
Maximum E.I.R.P. rating	(dBW)	Required value from every manufacturer	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes		
E.I.R.P. Adjustment Resolution in the Full Range of HPA power	(dB)		0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.25	0.25		
E.I.R.P. stability	(dB)	Integrated into antenna system mobile/maritime	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	1	1	1	1	1	1		
Automatic carrier mute, mandatory if mispointing exceeds	(deg)	mobile, auto-acquiring On-The-Move systems only	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	+/- 0.5°	+/- 0.5°	+/- 0.5°	+/- 0.5°	+/- 0.5°	+/- 0.5°		
Time within which the automatic carrier mute will have to take place	(ms)	mobile, auto-acquiring On-The-Move systems only	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	100 ms	100 ms	100 ms	100 ms	100 ms	100 ms		
Transmission to resume at (or less than) angle	(deg)	mobile, auto-acquiring On-The-Move systems only	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	± 0.2 within 1 sec	± 0.2 within 1 sec	± 0.2 within 1 sec	± 0.2 within 1 sec	± 0.2 within 1 sec	± 0.2 within 1 sec		
Transmit earth stations must be equipped with a receive chain which allows pointing optimization and tracking prior to and during transmissions			yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes		
Antenna RX gain at mid band frequency	(dBi)	For information only	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes		
Antenna RX frequency range	(GHz)	For information only	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes		
Add G/T value	(dB/K)	G/T referred to LNB input at 20° Elevation at 25°C (addition testing required at 10°C and 40°C) ambient temperature: Mid-Band Gain figure to be used Measurements includes OMT/Polarizer losses, for information only	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes		
General Remark	The individual satellite companies participating in this certification process are subject to trade control and sanctions laws that may restrict their ability to review and approve equipment proposed by certain vendors.																	